

OFFER No. 2407/217

(state Offer No. for communication)

Date: July 31, 2024

Farshid Tavakolian

Project Manager

+49-40-23546994

+49- 172-431 12 62

supply@delta-gmbh.eu

Delta Process Equipment GmbH

Adresse: Lübecker Straße 1, 22087

Hamburg, Deutschland

Dear Sir,

According to your inquiry we can offer you

1. L21/1220/A2"300lbsRF/N/Ex/B Magnetic Level Gauge **2 pcs**

Tag No.:	LT-RU0001A-03 + LG-RU0001A-03 LT-RU0001B-03 + LG-RU0001B-03
Lower Medium:	Liquid
Upper Medium:	Vapor
Lower Density:	436,9 kg/m ³
Upper Density:	10,22 kg/m ³
Operating temperature:	-0,07°C
Design temperature:	-45 to 120°C
Operating pressure:	4,7 bar g
Design pressure:	FV to 22 bar g
Measurement range:	1220 mm
Local indication:	full scale aluminium rail, red/white rollers
Scale:	no
Accuracy:	+/- 10 mm
Ingress protection:	IP65
Float:	Titanium
Connection:	Side-side, 2" 300lbsRF ASME B16.5, left side
Vent:	plug ½" NPT
Drain:	flanged, plug ½" NPT
Material:	316 SS
Electrical outputs:	no
Area classification:	hazardous
Insulation and heating:	no
Miscellaneous:	EN10204-3.1 material certificate, ATEX, SST tag plate, CE, PED
Price list:	2,580 €/pc
Discounted price:	1,935 €/pc

2. L21SR/762/A2"300lbsRF/N/Ex/B Reflex Glass Level Gauge **2 pcs**

Tag No.:	LG-RU0001A-02, LG-RU0001B-02
Lower Medium:	Liquid
Upper Medium:	Vapor
Lower Density:	436,9 kg/m ³
Upper Density:	10,22 kg/m ³
Operating temperature:	-0,07°C
Design temperature:	-45 to 120°C

Operating pressure:	4,7 bar g
Design pressure:	FV to 22 bar g
Measurement range :	762 mm
Local indication:	direct, reflex
Scale:	in mm, percentage %
Connection:	Side-side, 2" 300lbsRF ASME B16.5 + 2 valves, left side
Vent:	plug + valve
Drain:	plug + valve
Material:	tempered borosilicate glass, SS316L
Electrical outputs:	no
Area classification:	hazardous
Insulation and heating:	no
Other:	CERTIFICATE OF COMPLIANCE, 316SS NAMEPLATE

Price list: 2,240 €/pc

Discounted price: 1,680 €/pc

3. L21/H40/3/4"NPT/N/Ex Float Level Switch

2 pcs

Tag:	LS-RU0001A-01, LS-RU0001B-01
Medium:	Gases CNCG / steam / condensate
Density:	>800 kg/m ³
Design temperature:	100 °C
Ambient temperature:	+5 ... +40°C
Design pressure:	6 bar g
Float:	SS316
Ingress protection:	IP67
Accuracy:	1% of span
Material:	aluminium head, SS316 wetted parts
Process connection:	top-mounted, 3/4" NPT thread outer
Power supply:	230 VAC, 0.8 A, 25 W, M20x1.5 cable entry
Area classification:	hazardous
Miscellaneous:	SPDT switch-over contact

Price list: 960 €/pc

Discounted price: 720 €/pc

Discount: 25% off the price list. The freight cost and packing materials have not been included in the quotation.

See www.emkometer.com for more information.

Delivery term: EXW Ledec nad Sazavou, Czech Rep.

Payment: 100% in advance

Delivery time: 6 weeks

Guarantee: 24 months if not specified otherwise in the agreement

Offer validity: 2 months

We hope that our offer meets your requirements. If you have any questions, do not hesitate to contact us.
Best regards

Eng. Jiří Kroužek

EMKOMETER s. r. o.

Mob: +420 603 273 240