

	LIDCO, Pars SEE Zone, Assaluyeh, Integrated Methanol and Ammonia Plant 3000 MTPD MeOH / 900 MTPD NH3 PROJECT						
	Main Motor Data Sheets						
	Document No. 17735-10						Page
	Project No.	Vendor Doc.	P.O. No.	Department	Document Type	Serial No	Revision
	N278	VD	6019	PM	DS	0010	06
						Page 1 of 4	

**Airpack B.V. - Air Compressor –
Integrated Methanol and Ammonia Plant
17735-COM Main Motor Data Sheets (K020)**

06	03-07-2024	Issued for Approval	S.K.	S.K.	J.J.
05	01-07-2024	Issued for Approval	S.K.	S.K.	J.J.
04	21-06-2024	Issued for Approval	S.K.	S.K.	J.J.
03	10-06-2024	Issued for Approval	S.K.	S.K.	J.J.
02	03-06-2024	Issued for Approval	S.K.	S.K.	J.J.
01	08-04-2024	Issued for Approval	S.K.	S.K.	J.J.
REV.	DATE	DESCRIPTION	DRAWN	CHECKED	APPROVED

This document has been produced by Contractor for LIDCO. It is confidential and cannot be disclosed to or used by any third party for any purpose without prior written consent.

Main Motor Data Sheets

Document No. 17735-10

Page

Project No.	Vendor Doc.	P.O. No.	Department	Document Type	Serial No	Revision	Page
N278	VD	6019	PM	DS	0010	06	Page 2 of 4

LIST OF REVISED PAGES

Rev. Page	01	02	03	04	05	06	07	08	09	10	Rev. Page	01	02	03	04	05
1	X	X	X	X	X	X					51					76
2	X	X	X	X	X	X					52					77
3	X	X	X	X	X	X					53					78
4	X	X	X	X	X	X					54					79
5											55					80
6											56					81
7											57					82
8											58					83
9											59					84
10											60					85
11											61					86
12											62					87
13											63					88
14											64					89
15											65					90
16											66					91
17											67					92
18											68	ATTACHMENT				
19											69	1				
20											70	2				
21											71	3				
22											72	4				
23											73	5				
24											74	6				
25											75	7				



MAIN MOTOR DATA SHEET

PROJECT :	Integrated Methanol and Ammonia Plant	PROJECT N°:	UNIT	DOCUMENT N°	SHEET	REV
CLIENT:	LIDCO	17735	KM-020	N-278-VD-6019-PM-DS-0010	3 of 4	06

1	Item:	Main motor	Quantity:	1
2	General specificatio	N278-000-EL-JSS-1691-001	Standards, codes:	(IEC60034) IEC 60034-8
3	Supplier:	Airpack	Manufacturer:	Siemens
4			Unit	
5	ENVIRONMENTAL CONDITIONS			
6	Installation (indoor/outdoor) / Ambient Type		Indoor	
7	Ambient Design Temperature (Min./Max.)	°C	0-49	
8	Altitude (if > 1000m)	m	<1000 m.a.s.l.	
9	Relative Humidity	%	85%	
10	Area Classification		Safe area	
11	Other conditions		Onshore	
12				
13	DRIVEN MACHINE DATA			
14	Machine Type		Air booster compressor	
15	Max absorbed power	kW	Approx. 5	
16	Motor rated power	kW	11	
17	Coupling type		V-belt	
18	Starting current		7.4 xln	
19				
20	GENERAL MOTOR CHARACTERISTICS			
21	Rated power	kW	15	
22	Poles	N°	4	
23	Voltage	V	400+/-5%	
24	Frequency	Hz	50+/-2%	
25	phase	ph	3	
26	Motor type		Squirrel cage induction motor	
27	Fan execution		Standard	
28	Motor material		Cast Iron	
29	special execution		-	
30	Direction of Rotation (looking at motor coupling)		Clockwise	
31	Mounting		IM B35	
32	Protection degree enclosure	IP	55	
33	Protection degree terminal box	IP	55	
34	Atex protection Motor		-	
35	Atex protection terminal box		-	
36	Area Classification according ATEX		Safe area	
37	Axial Bearing Type (NDE)		Roller	
38	Bearing Code (NDE)		6309-C3	
39	Axial Bearing Type (DE)		Roller	
40	Bearing code (DE)		6309-C3	
41	Lubrication type		Esso unirex N3	
42	Lubrication interval	hr	4000	
43	Cooling method		TEFC	
44	Winding material		Copper	
45	Starting method		DOL	
46	Winding Connection		STAR	
47	Number of terminals brought out	N°	3	
48	Min.Insulation Class		F	
49	Max Temperature Rise		B	
50	Painting standard		C5M	
51	Painting Colour		RAL-7030	
52	Motor Nett Weight	Kg	217	
53	Dimension (L x W x H)	mm	725,5x350x545	
54	Frame Size	L	160	
55	Noise Level at 1 m (at full load)	dB(A)	69	
56	Full Load Speed	rpm	1467	
57	Power factor	100/75/50% load	0.82/0.82/0.72	
58	Max. voltage drop at starting	%	15	
59	Rated current	A	28	
60	Full load Torque	Nm	3,4	
61	Efficiency	100/75/50% load	92.1/92.3/91.5	
62	Power Factor 2/4		0,85	
63	Total no. of start per hour : hot		2	
64	Total no. of start per hour : Cold		3	
65	Duty type		S1	
66	Service Factor		1.0	

TO BE COMPLETED BY PURCHASER & BY DRIVEN MACHINE SUPPLIER

