

	LIDCO, Pars SEE Zone, Assaluyeh, Integrated Methanol and Ammonia Plant 3000 MTPD MeOH / 900 MTPD NH3 PROJECT						
	PSV Data Sheets						
	Document No. 17735-46						Page
	Project No.	Vendor Doc.	P.O. No.	Department	Document Type	Serial No	Revision
N278	VD	6019	IN	DS	0039	06	Page 1 of 7

**Airpack B.V. - Air Compressor –
Integrated Methanol and Ammonia Plant
17735-COM PSV Data Sheets (K020)**

06	25-06-2024	Issued for Approval	L.K.	J.J.	S.K.
05	08-05-2024	Issued for Approval	L.K.	J.J.	S.K.
04	17-04-2024	Issued for Approval	L.K.	J.J.	S.K.
03	26-03-2024	Issued for Approval	L.K.	J.J.	S.K.
02	11-03-2024	Issued for Approval	L.K.	J.J.	S.K.
01	08-11-2023	Issued for Approval	S.K.	J.J.	S.K.
REV.	DATE	DESCRIPTION	DRAWN	CHECKED	APPROVED

This document has been produced by Contractor for LIDCO. It is confidential and cannot be disclosed to or used by any third party for any purpose without prior written consent.

PSV Data Sheets

Document No. 17735-46

Page

Project No.	Vendor Doc.	P.O. No.	Department	Document Type	Serial No	Revision	Page
N278	VD	6019	IN	DS	0039	06	Page 2 of 7

LIST OF REVISED PAGES

Rev. Page	01	02	03	04	05	06	07	08	09	10	Rev. Page	01	02	03	04	05	Rev. Page	01	02	03	04	05
1	X	X	X	X	X	X					51						76					
2	X	X	X	X	X	X					52						77					
3	X	X	X	X	X	X					53						78					
4	X	X	X	X	X	X					54						79					
5	X	X	X	X	X	X					55						80					
6	X	X	X	X	X	X					56						81					
7	X	X	X	X	X	X					57						82					
8											58						83					
9											59						84					
10											60						85					
11											61						86					
12											62						87					
13											63						88					
14											64						89					
15											65						90					
16											66						91					
17											67						92					
18											68						ATTACHMENT					
19											69						1					
20											70						2					
21											71						3					
22											72						4					
23											73						5					
24											74						6					
25											75						7					



Doc. No : 17735-46

Rev. No. : 5

Page : 3 of 7


INDEX			
No.	Device	Tag Number	Page
1	Pressure Safety Valve	320PSV-8201	4
2	Pressure Safety Valve	320PSV-8202	5
3	Pressure Safety Valve	320PSV-8203	6
4	Pressure Safety Valve	320PSV-8204	7
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			

Note

06	LK	25-6-2024	Issue for Approval	INSTRUMENT AND VALVE DATASHEET Index	
05	LK	8-5-2024	Issue for Approval		
04	LK	17-4-2024	Issue for Approval		
03	LK	26-3-2024	Issue for Approval		
02	LK	11-3-2024	Issue for Approval		
01	SK	8-11-2023	Issue for Approval		
Rev	By	Date	Description		Sheet 3 of 7 Based on P&ID Rev.08


GENERAL	1	Tag Number		320PSV-8201	
	2	Service		Pressure Safety Valve	
	3	P&ID No.		N278-VD-6019-PR-PID-0002	
	4	Location		Package inlet	
	5	Line number		DAMPENER KV-020-001	
	6	Area classification		Safe area	
	7	Nozzle		Full nozzle	
	8	Design type		Safety	
	9	Conv., Bellows, Pilot op.		Conventional type	
	10	Bonnet Type		Closed	
	11	Bonnet connection		Bolted	
PROCESS CONDITIONS	12	Fluid	State	Air	Vapor
	13	Pressure	Inlet Max.	9,5 bar(g)	12,5 bar(g)
	14	Temperature	Norm. Max.	46 °C	-
	15	Design	Press. Temp.	12,5 bar(g)	75 °C
	16	Ambient Temp.	Min. Max.	-	-
	17	Flow		35 Nm ³ /hr	
BASIS AND SELECTION	18	Set Pressure		12,5 bar(g)	
	19	Molecular Weight	Oper. Sp. Gr.	-	-
	20	Back Pres. (bar(g))		ATM	
	21	Allowable Overpressure (%)		10%	
	22	Compressibility Factor (Z)		1	
	23	Ratio of Specific Heat (Cp/Cv)		-	
	24	Operating Viscosity (cP)		-	
	25	Barometric Pressure		1,013 bar(a)	
	26	Max. Allowable Relief Pressure		14,7 bar(a)	
	27	Design Code		API 520, 521, 526	
	28	Size Basis		Blocked discharge	
	29	Required discharge Area (sq.mm)		4,03 mm ²	
	30	Selected Area (sq.mm)		70,97 mm ²	
	31	Orifice Designation		D	
32	Noise level at 1m (from calculation)		101.74 dB		
33	Blow-down		5-7%		
CONNECTIONS	34	Inlet Size	Outlet Size	1"	2"
	35	Inlet Connection	Outlet Conn.	RF	RF
	36	Inlet Rating	Outlet Rating	300#	150#
	37				
MATERIAL	39	Body and Bonnet		SS316	
	40	Seat and Disc		SS316	
	41	Guide and Rings		SS316	
	42	Spring		SS316	
	43	Nozzle		SS316	
OPTIONS	44	Tag plate		SS316, Plate with steel wire	
	45	Test gag		Yes, with stamped tag number	
	46	Lever		Packed	
	47	Cap		Screwed	
CERTIFICATES	48	3.1 Material certificate		Yes	
	49	Calibration certificate		Yes	
	50	Leakage test acc to API STD 527		Yes	
	51	Functional test		No	
CALCULATIONS	52	Sizing calculation		Yes	
	53				
	54				
PURCHASE	55	Manufacturer		Broady	
	56	Model		3531D-SN-021A0	
	57				

NOTES :

06	LK	25-6-2024	Issue for Approval	INSTRUMENT AND VALVE DATASHEET Pressure Safety Valve 	Sheet 4 of 7 Based on P&ID Rev.08
05	LK	8-5-2024	Issue for Approval		
04	LK	17-4-2024	Issue for Approval		
03	LK	26-3-2024	Issue for Approval		
02	LK	11-3-2024	Issue for Approval		
01	SK	8-11-2023	Issue for Approval		
Rev	By	Date	Description		


GENERAL	1	Tag Number		320PSV-8202	
	2	Service		Pressure Safety Valve	
	3	P&ID No.		N278-VD-6019-PR-PID-0002	
	4	Location		1st stage discharge	
	5	Line number		DAMPENER KV-020-002	
	6	Area classification		Safe area	
	7	Nozzle		Full nozzle	
	8	Design type		Safety	
	9	Conv., Bellows, Pilot op.		Conventional type	
	10	Bonnet Type		Closed	
	11	Bonnet connection		Bolted	
PROCESS CONDITIONS	12	Fluid	State	Air	Vapor
	13	Pressure	Inlet Max.	23,3 bar(g)	30,5 bar(g)
	14	Temperature	Norm. Max.	157 °C	-
	15	Design	Press. Temp.	30,5 bar(g)	175 °C
	16	Ambient Temp.	Min. Max.	-	-
	17	Flow		35 Nm ³ /hr	
BASIS AND SELECTION	18	Set Pressure		30,5 bar(g)	
	19	Molecular Weight	Oper. Sp. Gr.	-	-
	20	Back Pres. (bar(g))		ATM	
	21	Allowable Overpressure (%)		10%	
	22	Compressibility Factor (Z)		1	
	23	Ratio of Specific Heat (Cp/Cv)		-	
	24	Operating Viscosity (cP)		-	
	25	Barometric Pressure		1,013 bar(a)	
	26	Max. Allowable Relief Pressure		34,5 bar(a)	
	27	Design Code		API 520, 521, 526	
	28	Size Basis		Blocked discharge	
	29	Required discharge Area (sq.mm)		1,95 mm ²	
	30	Selected Area (sq.mm)		70,97 mm ²	
	31	Orifice Designation		D	
32	Noise level at 1m (from calculation)		113,4 dB		
33	Blow-down		5-7%		
CONNECTIONS	34	Inlet Size	Outlet Size	1"	2"
	35	Inlet Connection	Outlet Conn.	RF	RF
	36	Inlet Rating	Outlet Rating	600#	150#
MATERIAL	37	Body and Bonnet		SS316	
	38	Seat and Disc		SS316	
	39	Guide and Rings		SS316	
	40	Spring		SS316	
	41	Nozzle		SS316	
	42				
OPTIONS	44	Tag plate		SS316, Plate with steel wire	
	45	Test gag		Yes, with stamped tag number	
	46	Lever		Packed	
	47	Cap		Screwed	
CERTIFICATES	48	3.1 Material certificate		Yes	
	49	Calibration certificate		Yes	
	50	Leakage test acc to API STD 527		Yes	
	51	Functional test		No	
CALCULATIONS	52	Sizing calculation		Yes	
	53				
	54				
PURCHASE	55	Manufacturer		Broady	
	56	Model		3551D-SN-021A0	
57					

NOTES :

06	LK	25-6-2024	Issue for Approval	INSTRUMENT AND VALVE DATASHEET Pressure Safety Valve 	Sheet 3 of 7 Based on P&ID Rev.08
05	LK	8-5-2024	Issue for Approval		
04	LK	17-4-2024	Issue for Approval		
03	LK	26-3-2024	Issue for Approval		
02	LK	11-3-2024	Issue for Approval		
01	SK	8-11-2023	Issue for Approval		
Rev	By	Date	Description		


GENERAL	1	Tag Number		320PSV-8203	
	2	Service		Pressure Safety Valve	
	3	P&ID No.		N278-VD-6019-PR-PID-0002	
	4	Location		2nd stage discharge	
	5	Line number		DAMPENER KV-020-004	
	6	Area classification		Safe area	
	7	Nozzle		Full nozzle	
	8	Design type		Safety	
	9	Conv., Bellows, Pilot op.		Conventional type	
	10	Bonnet Type		Closed	
	11	Bonnet connection		Bolted	
PROCESS CONDITIONS	12	Fluid	State	Air	Vapor
	13	Pressure	Inlet Max.	30 bar (g)	39 bar(g)
	14	Temperature	Norm. Max.	116°C	-
	15	Design	Press. Temp.	39 bar (g)	135 °C
	16	Ambient Temp.	Min. Max.	-	-
	17	Flow		35 Nm ³ /hr	
BASIS AND SELECTION	18	Set Pressure		39 bar(g)	
	19	Molecular Weight	Oper. Sp. Gr.	-	-
	20	Back Pres. (bar(g))		ATM	
	21	Allowable Overpressure (%)		10%	
	22	Compressibility Factor (Z)		1	
	23	Ratio of Specific Heat (Cp/Cv)		-	
	24	Operating Viscosity (cP)		-	
	25	Barometric Pressure		1,013 bar(a)	
	26	Max. Allowable Relief Pressure		43,9 bar(a)	
	27	Design Code		API 520, 521, 526	
	28	Size Basis		Blocked discharge	
	29	Required discharge Area (sq.mm)		1,47 mm ²	
	30	Selected Area (sq.mm)		70,97 mm ²	
	31	Orifice Designation		D	
32	Noise level at 1m (from calculation)		113,36 dB		
33	Blow-down		5-7%		
CONNECTIONS	34	Inlet Size	Outlet Size	1"	2"
	35	Inlet Connection	Outlet Conn.	RF	RF
	36	Inlet Rating	Outlet Rating	600#	150#
MATERIAL	37	Body and Bonnet		SS316	
	38	Seat and Disc		SS316	
	39	Guide and Rings		SS316	
	40	Spring		SS316	
	41	Nozzle		SS316	
	42				
OPTIONS	44	Tag plate		SS316, Plate with steel wire	
	45	Test gag		Yes, with stamped tag number	
	46	Lever		Packed	
	47	Cap		Screwed	
CERTIFICATES	48	3.1 Material certificate		Yes	
	49	Calibration certificate		Yes	
	50	Leakage test acc to API STD 527		Yes	
	51	Functional test		No	
CALCULATIONS	52	Sizing calculation		Yes	
	53				
	54				
PURCHASE	55	Manufacturer		Broady	
	56	Model		3551D-SN-021A0	
57					

NOTES :

06	LK	25-6-2024	Issue for Approval	INSTRUMENT AND VALVE DATASHEET Pressure Safety Valve 	Sheet 6 of 7 Based on P&ID Rev.08
05	LK	8-5-2024	Issue for Approval		
04	LK	17-4-2024	Issue for Approval		
03	LK	26-3-2024	Issue for Approval		
02	LK	11-3-2024	Issue for Approval		
01	SK	8-11-2023	Issue for Approval		
Rev	By	Date	Description		

GENERAL	1	Tag Number		320PSV-8204	
	2	Service		Pressure Safety Valve	
	3	P&ID No.		N278-VD-6019-PR-PID-0002	
	4	Location		Water system	
	5	Line number		3/4"-CWR-320-26-B24C-N	
	6	Area classification		Safe area	
	7	Nozzle		Full nozzle	
	8	Design type		Safety	
	9	Conv., Bellows, Pilot op.		Conventional type	
	10	Bonnet Type		Closed	
	11	Bonnet connection		Bolted	
PROCESS CONDITIONS	12	Fluid	State	Water	Liquid
	13	Pressure	Inlet Max.	4,4 bar(g)	
	14	Temperature	Norm. Max.		46 °C
	15	Design	Press. Temp.	7 bar(g)	75 °C
	16	Ambient Temp.	Min. Max.	-	-
TUBE RUPTURE CASE	17	Flow		1 Nm ³ /h	
	18	Fluid	State	Water/Air	Liquid/Gas
	19	Pressure	Temperature	max. 39 bar(g)	135 °C
	20	Flow on air side		35 Nm ³ /h	
BASIS AND SELECTION	21	Set Pressure		7 bar(g)	
	22	Molecular Weight	Oper. Sp. Gr.	-	-
	23	Back Pres. (bar(g))		ATM	
	24	Allowable Overpressure (%)		10%	
	25	Compressibility Factor (Z)		1	
	26	Ratio of Specific Heat (Cp/Cv)		-	
	27	Operating Viscosity (cP)		-	
	28	Barometric Pressure		1,013 bar(a)	
	29	Max. Allowable Relief Pressure		8,7 bar(a)	
	30	Design Code		API 520, 521	
	31	Size Basis		Tube rupture & thermal expansion	
	32	Required discharge Area (sq.mm)		7,4 mm ²	
	33	Selected Area (sq.mm)		25,81 mm ²	
	34	Orifice Designation		N/A	
35	Noise level at 1m (from calculation)		97,85 dB		
36	Blow-down		10-20%		
CONNECTIONS	37	Inlet Size	Outlet Size	3/4"	1"
	38	Inlet Connection	Outlet Conn.	NPT	NPT
	39	Inlet Rating	Outlet Rating	6000#	6000#
MATERIAL	40	Body and Bonnet		CS	
	41	Seat and Disc		SS316	
	42	Guide and Rings		SS316	
	43	Spring		SS316	
	44	Nozzle		SS316	
OPTIONS	45				
	46	Tag plate		SS316, Plate with steel wire	
	47	Test gag		Yes, with stamped tag number	
	48	Lever		Packed	
CERTIFICATES	49	Cap		Screwed	
	50	3.1 Material certificate		Yes	
	51	Calibration certificate		Yes	
	52	Leakage test acc to API STD 527		Yes	
CALCULATIONS	53	Functional test		No	
	54	Sizing calculation		Yes	
PURCHASE	55	Manufacturer		Broady	
	56	Model		26002-CN-021A1	
57					

NOTES :

06	LK	25-6-2024	Issue for Approval	INSTRUMENT AND VALVE DATASHEET Pressure Safety Valve 	Sheet 7 of 7 Based on P&ID Rev.08
05	LK	8-5-2024	Issue for Approval		
04	LK	17-4-2024	Issue for Approval		
03	LK	26-3-2024	Issue for Approval		
02	LK	11-3-2024	Issue for Approval		
01	SK	8-11-2023	Issue for Approval		
Rev	By	Date	Description		